

Fluid
Bed
Drying
Series



Fluid Bed Drying Series



■ Specifications and dimensions are subject to change without prior notice.

Granulation Line



D Series



DE Series



SM Series



D/DE Series



Vacuum Transmitter / IBC

Description									
		100	200	300	400	500	600	800	1000
Container Capacity (ℓ)		100	200	300	400	500	600	800	1,000
Fan	Air Volume (CMM)	10	30	40	50	60	70	100	120
	Air Volume Pressure (mmAq)	1,250							
	Power Consumption (kW)	15	19	22	30	38	45	60	80
Heating	Temperature Range (°C)	80							
	Heating Volume (kW)	65	90	110	130	155	175	220	270
Dimension (mm)	Machine Outer Diameter (∅)	700	870	1,000	1,100	1,185	1,260	1,400	1,600
	Width (W)	1,200 (1,300)	1,380 (1,370)	1,500	1,600	1,685	1,760	1,900	2,050
	Height (H)	3,150 (3,500)	3,500 (4,000)	3,700 (4,560)	3,900 (4,780)	4,200 (4,700)	4,500 (5,000)	4,800 (5,300)	5,100 (5,600)
Power Supply		200, 220, 380, 400, 415, 440, 480V, 50/60Hz, 3Ph							

• () Dimension is DE Series.